



## SN74LVC1G00 Single 2-Input Positive-NAND Gate

### 1 Features

- Available in the Ultra Small 0.64-mm<sup>2</sup> Package (DPW) With 0.5-mm Pitch
- Supports 5-V V<sub>CC</sub> Operation
- Inputs Accept Voltages to 5.5 V
- Provides Down Translation to V<sub>CC</sub>
- Max t<sub>pd</sub> of 3.8 ns at 3.3 V
- Low Power Consumption, 10-μA Max I<sub>CC</sub>
- ±24-mA Output Drive at 3.3 V
- I<sub>off</sub> Supports Live Insertion, Partial-Power-Down Mode, and Back Drive Protection
- Latch-Up Performance Exceeds 100 mA Per JESD 78, Class II
- ESD Protection Exceeds JESD 22
  - 2000-V Human-Body Model (A114-A)
  - 1000-V Charged-Device Model (C101)

### 2 Applications

- AV Receiver
- Audio Dock: Portable
- Blu-ray Player and Home Theater
- Embedded PC
- MP3 Player/Recorder (Portable Audio)
- Personal Digital Assistant (PDA)
- Power: Telecom/Server AC/DC Supply: Single Controller: Analog and Digital
- Solid State Drive (SSD): Client and Enterprise
- TV: LCD/Digital and High-Definition (HDTV)
- Tablet: Enterprise
- Video Analytics: Server
- Wireless Headset, Keyboard, and Mouse

### 4 Simplified Schematic



### 3 Description

This single 2-input positive-NAND gate is designed for 1.65-V to 5.5-V V<sub>CC</sub> operation.

The SN74LVC1G00 performs the Boolean function  $Y = A \times B$  or  $Y = \overline{A + B}$  in positive logic.

The CMOS device has high output drive while maintaining low static power dissipation over a broad V<sub>CC</sub> operating range.

The SN74LVC1G00 is available in a variety of packages, including the ultra-small DPW package with a body size of 0.8 mm × 0.8 mm.

**Device Information<sup>(1)</sup>**

| DEVICE NAME | PACKAGE    | BODY SIZE       |
|-------------|------------|-----------------|
| SN74LVC1G00 | SOT-23 (5) | 2.9mm × 1.6mm   |
|             | SC70 (5)   | 2.0mm × 1.25mm  |
|             | X2SON (4)  | 0.8mm × 0.8mm   |
|             | SON (6)    | 1.45mm × 1.0mm  |
|             | DSBGA (5)  | 1.41mm × 0.91mm |

(1) For all available packages, see the orderable addendum at the end of the datasheet.



## Table of Contents

|                                                                           |          |                                                            |           |
|---------------------------------------------------------------------------|----------|------------------------------------------------------------|-----------|
| <b>1 Features</b>                                                         | <b>1</b> | <b>9 Detailed Description</b>                              | <b>9</b>  |
| <b>2 Applications</b>                                                     | <b>1</b> | 9.1 Overview                                               | 9         |
| <b>3 Description</b>                                                      | <b>1</b> | 9.2 Functional Block Diagram                               | 9         |
| <b>4 Simplified Schematic</b>                                             | <b>1</b> | 9.3 Feature Description                                    | 9         |
| <b>5 Revision History</b>                                                 | <b>2</b> | 9.4 Device Functional Modes                                | 9         |
| <b>6 Pin Configuration and Functions</b>                                  | <b>3</b> | <b>10 Application and Implementation</b>                   | <b>10</b> |
| <b>7 Specifications</b>                                                   | <b>3</b> | 10.1 Application Information                               | 10        |
| 7.1 Absolute Maximum Ratings                                              | 3        | 10.2 Typical Application                                   | 10        |
| 7.2 Handling Ratings                                                      | 3        | <b>11 Power Supply Recommendations</b>                     | <b>11</b> |
| 7.3 Recommended Operating Conditions                                      | 4        | <b>12 Layout</b>                                           | <b>11</b> |
| 7.4 Thermal Information                                                   | 4        | 12.1 Layout Guidelines                                     | 11        |
| 7.5 Electrical Characteristics                                            | 5        | 12.2 Layout Example                                        | 11        |
| 7.6 Switching Characteristics, $C_L = 15\text{ pF}$                       | 5        | <b>13 Device and Documentation Support</b>                 | <b>12</b> |
| 7.7 Switching Characteristics, $-40^\circ\text{C}$ to $85^\circ\text{C}$  | 5        | 13.1 Trademarks                                            | 12        |
| 7.8 Switching Characteristics, $-40^\circ\text{C}$ to $125^\circ\text{C}$ | 5        | 13.2 Electrostatic Discharge Caution                       | 12        |
| 7.9 Operating Characteristics                                             | 6        | 13.3 Glossary                                              | 12        |
| 7.10 Typical Characteristics                                              | 6        | <b>14 Mechanical, Packaging, and Orderable Information</b> | <b>12</b> |
| <b>8 Parameter Measurement Information</b>                                | <b>7</b> |                                                            |           |

## 5 Revision History


| Changes from Revision AA (March 2014) to Revision AB | Page |
|------------------------------------------------------|------|
| • Added Pin Functions table.                         | 3    |
| • Updated Handling Ratings table.                    | 3    |
| • Added Thermal Information table.                   | 4    |
| • Added Typical Characteristics.                     | 6    |
| • Added Detailed Description section.                | 9    |
| • Added Application and Implementation section.      | 10   |
| • Added Power Supply Recommendations section.        | 11   |
| • Added Layout section.                              | 11   |

| Changes from Revision Z (November 2014) to Revision AA | Page |
|--------------------------------------------------------|------|
| • Added Applications section.                          | 1    |
| • Added Device Information table.                      | 1    |
| • Added $T_{\text{stg}}$ to Handling Ratings table.    | 3    |

| Changes from Revision Y (September 2013) to Revision Z | Page |
|--------------------------------------------------------|------|
| • Changed document Features.                           | 1    |

| Changes from Revision X (November 2012) to Revision Y                             | Page |
|-----------------------------------------------------------------------------------|------|
| • Extended operating temperature from $85^\circ\text{C}$ to $125^\circ\text{C}$ . | 4    |

## 6 Pin Configuration and Functions



### Pin Functions

| PIN             |                    |          |     | DESCRIPTION   |
|-----------------|--------------------|----------|-----|---------------|
| NAME            | DBV, DCK, DRL, YZP | DRY, DSF | DPW |               |
| A               | 1                  | 1        | 2   | Input         |
| B               | 2                  | 2        | 1   | Input         |
| GND             | 3                  | 3        | 3   | Ground        |
| Y               | 4                  | 4        | 4   | Output        |
| V <sub>CC</sub> | 5                  | 6        | 5   | Power pin     |
| NC              |                    | 5        |     | Not connected |

## 7 Specifications

### 7.1 Absolute Maximum Ratings<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted)

|                                                                                                            | MIN  | MAX                   | UNIT |
|------------------------------------------------------------------------------------------------------------|------|-----------------------|------|
| V <sub>CC</sub> Supply voltage range                                                                       | –0.5 | 6.5                   | V    |
| V <sub>I</sub> Input voltage range                                                                         | –0.5 | 6.5                   | V    |
| V <sub>O</sub> Voltage range applied to any output in the high-impedance or power-off state <sup>(2)</sup> | –0.5 | 6.5                   | V    |
| V <sub>O</sub> Voltage range applied to any output in the high or low state <sup>(2)(3)</sup>              | –0.5 | V <sub>CC</sub> + 0.5 | V    |
| I <sub>IK</sub> Input clamp current                                                                        |      | –50                   | mA   |
| I <sub>OK</sub> Output clamp current                                                                       |      | –50                   | mA   |
| I <sub>O</sub> Continuous output current                                                                   |      | ±50                   | mA   |
| Continuous current through V <sub>CC</sub> or GND                                                          |      | ±100                  | mA   |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The input and output negative-voltage ratings may be exceeded if the input and output current ratings are observed.
- (3) The value of V<sub>CC</sub> is provided in the *Recommended Operating Conditions* table.

### 7.2 Handling Ratings

|                                            | MIN                                                                                      | MAX | UNIT |
|--------------------------------------------|------------------------------------------------------------------------------------------|-----|------|
| T <sub>stg</sub> Storage temperature range | –65                                                                                      | 150 | °C   |
| V <sub>(ESD)</sub> Electrostatic discharge | Human body model (HBM), per ANSI/ESDA/JEDEC JS-001, all pins <sup>(1)</sup>              | 0   | 2000 |
|                                            | Charged device model (CDM), per JEDEC specification JESD22-C101, all pins <sup>(2)</sup> | 0   | 1000 |

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
- (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

**SN74LVC1G00**

SCES212AB – APRIL 1999 – REVISED APRIL 2014

[www.ti.com](http://www.ti.com)
**7.3 Recommended Operating Conditions<sup>(1)</sup>**

|                 |                                    | MIN                                             | MAX                    | UNIT |
|-----------------|------------------------------------|-------------------------------------------------|------------------------|------|
| V <sub>CC</sub> | Supply voltage                     | Operating                                       | 1.65                   | 5.5  |
|                 |                                    | Data retention only                             | 1.5                    |      |
| V <sub>IH</sub> | High-level input voltage           | V <sub>CC</sub> = 1.65 V to 1.95 V              | 0.65 × V <sub>CC</sub> | V    |
|                 |                                    | V <sub>CC</sub> = 2.3 V to 2.7 V                | 1.7                    |      |
|                 |                                    | V <sub>CC</sub> = 3 V to 3.6 V                  | 2                      |      |
|                 |                                    | V <sub>CC</sub> = 4.5 V to 5.5 V                | 0.7 × V <sub>CC</sub>  |      |
| V <sub>IL</sub> | Low-level input voltage            | V <sub>CC</sub> = 1.65 V to 1.95 V              | 0.35 × V <sub>CC</sub> | V    |
|                 |                                    | V <sub>CC</sub> = 2.3 V to 2.7 V                | 0.7                    |      |
|                 |                                    | V <sub>CC</sub> = 3 V to 3.6 V                  | 0.8                    |      |
|                 |                                    | V <sub>CC</sub> = 4.5 V to 5.5 V                | 0.3 × V <sub>CC</sub>  |      |
| V <sub>I</sub>  | Input voltage                      | 0                                               | 5.5                    | V    |
| V <sub>O</sub>  | Output voltage                     | 0                                               | V <sub>CC</sub>        | V    |
| I <sub>OH</sub> | High-level output current          | V <sub>CC</sub> = 1.65 V                        | –4                     | mA   |
|                 |                                    | V <sub>CC</sub> = 2.3 V                         | –8                     |      |
|                 |                                    | V <sub>CC</sub> = 3 V                           | –16                    |      |
|                 |                                    | V <sub>CC</sub> = 4.5 V                         | –24                    |      |
| I <sub>OL</sub> | Low-level output current           | V <sub>CC</sub> = 1.65 V                        | 4                      | mA   |
|                 |                                    | V <sub>CC</sub> = 2.3 V                         | 8                      |      |
|                 |                                    | V <sub>CC</sub> = 3 V                           | 16                     |      |
|                 |                                    | V <sub>CC</sub> = 4.5 V                         | 24                     |      |
| Δt/Δv           | Input transition rise or fall rate | V <sub>CC</sub> = 1.8 V ± 0.15 V, 2.5 V ± 0.2 V | 20                     | ns/V |
|                 |                                    | V <sub>CC</sub> = 3.3 V ± 0.3 V                 | 10                     |      |
|                 |                                    | V <sub>CC</sub> = 5 V ± 0.5 V                   | 5                      |      |
| T <sub>A</sub>  | Operating free-air temperature     | –40                                             | 125                    | °C   |

(1) All unused inputs of the device must be held at V<sub>CC</sub> or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number [SCBA004](#).

**7.4 Thermal Information**

| THERMAL METRIC <sup>(1)</sup> |                                              | SN74LVC1G00 |        |        |        |        |        | UNIT |
|-------------------------------|----------------------------------------------|-------------|--------|--------|--------|--------|--------|------|
|                               |                                              | DBV         | DCK    | DRL    | DRY    | YZP    | DPW    |      |
|                               |                                              | 5 PINS      | 5 PINS | 5 PINS | 6 PINS | 5 PINS | 4 PINS |      |
| R <sub>θJA</sub>              | Junction-to-ambient thermal resistance       | 229         | 278    | 243    | 439    | 130    | 340    | °C/W |
| R <sub>θJC(top)</sub>         | Junction-to-case (top) thermal resistance    | 164         | 93     | 78     | 277    | 54     | 215    |      |
| R <sub>θJB</sub>              | Junction-to-board thermal resistance         | 62          | 65     | 78     | 271    | 51     | 294    |      |
| Ψ <sub>JT</sub>               | Junction-to-top characterization parameter   | 44          | 2      | 10     | 84     | 1      | 41     |      |
| Ψ <sub>JB</sub>               | Junction-to-board characterization parameter | 62          | 64     | 77     | 271    | 50     | 294    |      |
| R <sub>θJC(bot)</sub>         | Junction-to-case (bottom) thermal resistance | –           | –      | –      | –      | –      | 250    |      |

(1) For more information about traditional and new thermal metrics, see the *IC Package Thermal Metrics* application report, [SPRA953](#).

## 7.5 Electrical Characteristics

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER        |               | TEST CONDITIONS                                                                 | V <sub>CC</sub> | –40°C to 85°C         |                    |     | RECOMMENDED<br>–40°C to 125°C |                    |     | UNIT |
|------------------|---------------|---------------------------------------------------------------------------------|-----------------|-----------------------|--------------------|-----|-------------------------------|--------------------|-----|------|
|                  |               |                                                                                 |                 | MIN                   | TYP <sup>(1)</sup> | MAX | MIN                           | TYP <sup>(1)</sup> | MAX |      |
| V <sub>OH</sub>  |               | I <sub>OH</sub> = –100 μA                                                       | 1.65 V to 5.5 V | V <sub>CC</sub> – 0.1 |                    |     | V <sub>CC</sub> – 0.1         |                    |     | V    |
|                  |               | I <sub>OH</sub> = –4 mA                                                         | 1.65 V          | 1.2                   |                    |     | 1.2                           |                    |     |      |
|                  |               | I <sub>OH</sub> = –8 mA                                                         | 2.3 V           | 1.9                   |                    |     | 1.9                           |                    |     |      |
|                  |               | I <sub>OH</sub> = –16 mA                                                        | 3 V             | 2.4                   |                    |     | 2.4                           |                    |     |      |
|                  |               | I <sub>OH</sub> = –24 mA                                                        |                 | 2.3                   |                    |     | 2.3                           |                    |     |      |
|                  |               | I <sub>OH</sub> = –32 mA                                                        | 4.5 V           | 3.8                   |                    |     | 3.8                           |                    |     |      |
| V <sub>OL</sub>  |               | I <sub>OL</sub> = 100 μA                                                        | 1.65 V to 5.5 V | 0.1                   |                    |     | 0.1                           |                    |     | V    |
|                  |               | I <sub>OL</sub> = 4 mA                                                          | 1.65 V          | 0.45                  |                    |     | 0.45                          |                    |     |      |
|                  |               | I <sub>OL</sub> = 8 mA                                                          | 2.3 V           | 0.3                   |                    |     | 0.3                           |                    |     |      |
|                  |               | I <sub>OL</sub> = 16 mA                                                         | 3 V             | 0.4                   |                    |     | 0.4                           |                    |     |      |
|                  |               | I <sub>OL</sub> = 24 mA                                                         |                 | 0.55                  |                    |     | 0.55                          |                    |     |      |
|                  |               | I <sub>OL</sub> = 32 mA                                                         | 4.5 V           | 0.55                  |                    |     | 0.55                          |                    |     |      |
| I <sub>I</sub>   | A or B inputs | V <sub>I</sub> = 5.5 V or GND                                                   | 0 to 5.5 V      | ±5                    |                    |     | ±5                            |                    |     | μA   |
| I <sub>off</sub> |               | V <sub>I</sub> or V <sub>O</sub> = 5.5 V                                        | 0               | ±10                   |                    |     | ±10                           |                    |     | μA   |
| I <sub>CC</sub>  |               | V <sub>I</sub> = 5.5 V or GND    I <sub>O</sub> = 0                             | 1.65 V to 5.5 V | 10                    |                    |     | 10                            |                    |     | μA   |
| ΔI <sub>CC</sub> |               | One input at V <sub>CC</sub> – 0.6 V,<br>Other inputs at V <sub>CC</sub> or GND | 3 V to 5.5 V    | 500                   |                    |     | 500                           |                    |     | μA   |
| C <sub>i</sub>   |               | V <sub>I</sub> = V <sub>CC</sub> or GND                                         | 3.3 V           | 4                     |                    |     | 4                             |                    |     | pF   |

(1) All typical values are at V<sub>CC</sub> = 3.3 V, T<sub>A</sub> = 25°C.

## 7.6 Switching Characteristics, C<sub>L</sub> = 15 pF

over recommended operating free-air temperature range (unless otherwise noted) (see [Figure 3](#))

| PARAMETER       | FROM<br>(INPUT) | TO<br>(OUTPUT) | –40°C to 85°C                       |     |                                    |     |                                    |     |                                  |     | UNIT |
|-----------------|-----------------|----------------|-------------------------------------|-----|------------------------------------|-----|------------------------------------|-----|----------------------------------|-----|------|
|                 |                 |                | V <sub>CC</sub> = 1.8 V<br>± 0.15 V |     | V <sub>CC</sub> = 2.5 V<br>± 0.2 V |     | V <sub>CC</sub> = 3.3 V<br>± 0.3 V |     | V <sub>CC</sub> = 5 V<br>± 0.5 V |     |      |
|                 |                 |                | MIN                                 | MAX | MIN                                | MAX | MIN                                | MAX | MIN                              | MAX |      |
| t <sub>pd</sub> | A or B          | Y              | 2.2                                 | 7.2 | 0.9                                | 4.4 | 0.8                                | 3.8 | 0.8                              | 3.4 | ns   |

## 7.7 Switching Characteristics, –40°C to 85°C

over recommended operating free-air temperature range, C<sub>L</sub> = 30 pF or 50 pF (unless otherwise noted) (see [Figure 4](#))

| PARAMETER       | FROM<br>(INPUT) | TO<br>(OUTPUT) | –40°C to 85°C                       |     |                                    |     |                                    |     |                                  |     | UNIT |
|-----------------|-----------------|----------------|-------------------------------------|-----|------------------------------------|-----|------------------------------------|-----|----------------------------------|-----|------|
|                 |                 |                | V <sub>CC</sub> = 1.8 V<br>± 0.15 V |     | V <sub>CC</sub> = 2.5 V<br>± 0.2 V |     | V <sub>CC</sub> = 3.3 V<br>± 0.3 V |     | V <sub>CC</sub> = 5 V<br>± 0.5 V |     |      |
|                 |                 |                | MIN                                 | MAX | MIN                                | MAX | MIN                                | MAX | MIN                              | MAX |      |
| t <sub>pd</sub> | A or B          | Y              | 3.1                                 | 9   | 1.3                                | 5.5 | 1                                  | 4.7 | 1                                | 4   | ns   |

## 7.8 Switching Characteristics, –40°C to 125°C

over recommended operating free-air temperature range, C<sub>L</sub> = 30 pF or 50 pF (unless otherwise noted) (see [Figure 4](#))

| PARAMETER       | FROM<br>(INPUT) | TO<br>(OUTPUT) | RECOMMENDED<br>–40°C to 125°C       |     |                                    |     |                                    |     |                                  |     | UNIT |
|-----------------|-----------------|----------------|-------------------------------------|-----|------------------------------------|-----|------------------------------------|-----|----------------------------------|-----|------|
|                 |                 |                | V <sub>CC</sub> = 1.8 V<br>± 0.15 V |     | V <sub>CC</sub> = 2.5 V<br>± 0.2 V |     | V <sub>CC</sub> = 3.3 V<br>± 0.3 V |     | V <sub>CC</sub> = 5 V<br>± 0.5 V |     |      |
|                 |                 |                | MIN                                 | MAX | MIN                                | MAX | MIN                                | MAX | MIN                              | MAX |      |
| t <sub>pd</sub> | A or B          | Y              | 3.1                                 | 9.7 | 1.3                                | 5.8 | 1                                  | 5   | 1                                | 4.3 | ns   |
| t <sub>pd</sub> | A               | Y              | 2                                   | 6.4 | 1                                  | 4.2 | 0.7                                | 3.3 | 0.7                              | 3.1 | ns   |

# SN74LVC1G00

SCES212AB – APRIL 1999 – REVISED APRIL 2014



www.ti.com

## 7.9 Operating Characteristics


$T_A = 25^\circ\text{C}$

| PARAMETER                              | TEST CONDITIONS     | $V_{CC} = 1.8\text{ V}$ | $V_{CC} = 2.5\text{ V}$ | $V_{CC} = 3.3\text{ V}$ | $V_{CC} = 5\text{ V}$ | UNIT |
|----------------------------------------|---------------------|-------------------------|-------------------------|-------------------------|-----------------------|------|
|                                        |                     | TYP                     | TYP                     | TYP                     | TYP                   |      |
| $C_{pd}$ Power dissipation capacitance | $f = 10\text{ MHz}$ | 22                      | 22                      | 23                      | 25                    | pF   |

## 7.10 Typical Characteristics







## 8 Parameter Measurement Information



| TEST              | S1         |
|-------------------|------------|
| $t_{PLH}/t_{PHL}$ | Open       |
| $t_{PLZ}/t_{PZL}$ | $V_{LOAD}$ |
| $t_{PHZ}/t_{PZH}$ | GND        |


| $V_{CC}$                         | INPUTS   |                      | $V_M$      | $V_{LOAD}$        | $C_L$ | $R_L$        | $V_{\Delta}$ |
|----------------------------------|----------|----------------------|------------|-------------------|-------|--------------|--------------|
|                                  | $V_I$    | $t_i/t_r$            |            |                   |       |              |              |
| $1.8\text{ V} \pm 0.15\text{ V}$ | $V_{CC}$ | $\leq 2\text{ ns}$   | $V_{CC}/2$ | $2 \times V_{CC}$ | 15 pF | 1 M $\Omega$ | 0.15 V       |
| $2.5\text{ V} \pm 0.2\text{ V}$  | $V_{CC}$ | $\leq 2\text{ ns}$   | $V_{CC}/2$ | $2 \times V_{CC}$ | 15 pF | 1 M $\Omega$ | 0.15 V       |
| $3.3\text{ V} \pm 0.3\text{ V}$  | 3 V      | $\leq 2.5\text{ ns}$ | 1.5 V      | 6 V               | 15 pF | 1 M $\Omega$ | 0.3 V        |
| $5\text{ V} \pm 0.5\text{ V}$    | $V_{CC}$ | $\leq 2.5\text{ ns}$ | $V_{CC}/2$ | $2 \times V_{CC}$ | 15 pF | 1 M $\Omega$ | 0.3 V        |



- NOTES:
- $C_L$  includes probe and jig capacitance.
  - Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
  - All input pulses are supplied by generators having the following characteristics: PRR  $\leq 10\text{ MHz}$ ,  $Z_o = 50\ \Omega$ .
  - The outputs are measured one at a time, with one transition per measurement.
  - $t_{PLZ}$  and  $t_{PHZ}$  are the same as  $t_{dis}$ .
  - $t_{PZL}$  and  $t_{PZH}$  are the same as  $t_{en}$ .
  - $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{pd}$ .
  - All parameters and waveforms are not applicable to all devices.





Figure 3. Load Circuit and Voltage Waveforms

## Parameter Measurement Information (continued)



| TEST              | S1         |
|-------------------|------------|
| $t_{PLH}/t_{PHL}$ | Open       |
| $t_{PLZ}/t_{PZL}$ | $V_{LOAD}$ |
| $t_{PHZ}/t_{PZH}$ | GND        |

| $V_{CC}$                         | INPUTS   |                      | $V_M$      | $V_{LOAD}$        | $C_L$ | $R_L$        | $V_{\Delta}$ |
|----------------------------------|----------|----------------------|------------|-------------------|-------|--------------|--------------|
|                                  | $V_I$    | $t_r/t_f$            |            |                   |       |              |              |
| $1.8\text{ V} \pm 0.15\text{ V}$ | $V_{CC}$ | $\leq 2\text{ ns}$   | $V_{CC}/2$ | $2 \times V_{CC}$ | 30 pF | 1 k $\Omega$ | 0.15 V       |
| $2.5\text{ V} \pm 0.2\text{ V}$  | $V_{CC}$ | $\leq 2\text{ ns}$   | $V_{CC}/2$ | $2 \times V_{CC}$ | 30 pF | 500 $\Omega$ | 0.15 V       |
| $3.3\text{ V} \pm 0.3\text{ V}$  | 3 V      | $\leq 2.5\text{ ns}$ | 1.5 V      | 6 V               | 50 pF | 500 $\Omega$ | 0.3 V        |
| $5\text{ V} \pm 0.5\text{ V}$    | $V_{CC}$ | $\leq 2.5\text{ ns}$ | $V_{CC}/2$ | $2 \times V_{CC}$ | 50 pF | 500 $\Omega$ | 0.3 V        |



- NOTES:
- $C_L$  includes probe and jig capacitance.
  - Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
  - All input pulses are supplied by generators having the following characteristics:  $PRR \leq 10\text{ MHz}$ ,  $Z_o = 50\ \Omega$ .
  - The outputs are measured one at a time, with one transition per measurement.
  - $t_{PLZ}$  and  $t_{PHZ}$  are the same as  $t_{dis}$ .
  - $t_{PZL}$  and  $t_{PZH}$  are the same as  $t_{on}$ .
  - $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{pd}$ .
  - All parameters and waveforms are not applicable to all devices.

**Figure 4. Load Circuit and Voltage Waveforms**

## 9 Detailed Description

### 9.1 Overview

The SN74LVC1G00 device contains one 2-input positive-NAND gate and performs the Boolean function  $Y = A \times B$  or  $Y = \overline{A + B}$ . This device is fully specified for partial-power-down applications using  $I_{off}$ . The  $I_{off}$  circuitry disables the outputs, preventing damaging current backflow through the device when it is powered down.

The DPW package technology is a major breakthrough in IC packaging. Its tiny 0.64 mm square footprint saves significant board space over other package options while still retaining the traditional manufacturing friendly lead pitch of 0.5 mm.

### 9.2 Functional Block Diagram



### 9.3 Feature Description

- Wide operating voltage range.
  - Operates from 1.65 V to 5.5 V.
- Allows down voltage translation.
- Inputs accept voltages to 5.5 V.
- $I_{off}$  feature allows voltages on the inputs and outputs, when  $V_{CC}$  is 0 V.

### 9.4 Device Functional Modes

**Function Table**


| INPUTS |   | OUTPUT<br>Y |
|--------|---|-------------|
| A      | B |             |
| H      | H | L           |
| L      | X | H           |
| X      | L | H           |

## 10 Application and Implementation

### 10.1 Application Information

The SN74LVC1G00 is a high drive CMOS device that can be used for implementing NAND logic with a high output drive, such as an LED application. It can produce 24 mA of drive current at 3.3 V making it ideal for driving multiple outputs and good for high speed applications up to 100 MHz. The inputs are 5.5 V tolerant allowing it to translate down to  $V_{CC}$ .

### 10.2 Typical Application



#### 10.2.1 Design Requirements

This device uses CMOS technology and has balanced output drive. Care should be taken to avoid bus contention because it can drive currents that would exceed maximum limits. The high drive will also create fast edges into light loads so routing and load conditions should be considered to prevent ringing.

#### 10.2.2 Detailed Design Procedure

##### 1. Recommended Input Conditions


- Rise time and fall time specs. See ( $\Delta t/\Delta V$ ) in [Recommended Operating Conditions](#) table.
- Specified high and low levels. See ( $V_{IH}$  and  $V_{IL}$ ) in [Recommended Operating Conditions](#) table.
- Inputs are overvoltage tolerant allowing them to go as high as ( $V_I$  max) in the [Recommended Operating Conditions](#) table at any valid  $V_{CC}$ .

##### 2. Recommend Output Conditions

- Load currents should not exceed ( $I_O$  max) per output and should not exceed total current (continuous current through  $V_{CC}$  or GND) for the part. These limits are located in the [Absolute Maximum Ratings](#) table.
- Outputs should not be pulled above  $V_{CC}$ .

## Typical Application (continued)

### 10.2.3 Application Curves



## 11 Power Supply Recommendations

The power supply can be any voltage between the min and max supply voltage rating located in the [Recommended Operating Conditions](#) table.


Each Vcc pin should have a good bypass capacitor to prevent power disturbance. For devices with a single supply a 0.1-μF capacitor is recommended and if there are multiple Vcc pins then a 0.01-μF or 0.022-μF capacitor is recommended for each power pin. It is ok to parallel multiple bypass caps to reject different frequencies of noise. 0.1-μF and 1-μF capacitors are commonly used in parallel. The bypass capacitor should be installed as close to the power pin as possible for best results.

## 12 Layout

### 12.1 Layout Guidelines

When using multiple bit logic devices inputs should not ever float. In many cases, functions or parts of functions of digital logic devices are unused; for example, when only two inputs of a triple-input AND gate are used or only 3 of the 4 buffer gates are used. Such input pins should not be left unconnected because the undefined voltages at the outside connections result in undefined operational states. Specified below are the rules that must be observed under all circumstances. All unused inputs of digital logic devices must be connected to a high or low bias to prevent them from floating. The logic level that should be applied to any particular unused input depends on the function of the device. Generally they will be tied to Gnd or Vcc whichever make more sense or is more convenient.

### 12.2 Layout Example



## 13 Device and Documentation Support

### 13.1 Trademarks

All trademarks are the property of their respective owners.

### 13.2 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

### 13.3 Glossary

[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms and definitions.

## 14 Mechanical, Packaging, and Orderable Information

The following pages include mechanical packaging and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

## PACKAGING INFORMATION

| Orderable Device  | Status<br>(1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan<br>(2) | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5)                              | Samples                 |
|-------------------|---------------|--------------|-----------------|------|-------------|-----------------|--------------------------------------|----------------------|--------------|------------------------------------------------------|-------------------------|
| SN74LVC1G00DBVR   | ACTIVE        | SOT-23       | DBV             | 5    | 3000        | RoHS & Green    | NIPDAU   SN                          | Level-1-260C-UNLIM   | -40 to 125   | (C005, C00F, C00J, C00K, C00R)<br>(C00H, C00P, C00S) | <a href="#">Samples</a> |
| SN74LVC1G00DBVRE4 | ACTIVE        | SOT-23       | DBV             | 5    | 3000        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | C00F                                                 | <a href="#">Samples</a> |
| SN74LVC1G00DBVRG4 | ACTIVE        | SOT-23       | DBV             | 5    | 3000        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | C00F                                                 | <a href="#">Samples</a> |
| SN74LVC1G00DBVT   | ACTIVE        | SOT-23       | DBV             | 5    | 250         | RoHS & Green    | NIPDAU   SN                          | Level-1-260C-UNLIM   | -40 to 125   | (C005, C00F, C00J, C00K, C00R)<br>(C00H, C00P, C00S) | <a href="#">Samples</a> |
| SN74LVC1G00DBVTE4 | ACTIVE        | SOT-23       | DBV             | 5    | 250         | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | C00F                                                 | <a href="#">Samples</a> |
| SN74LVC1G00DBVTG4 | ACTIVE        | SOT-23       | DBV             | 5    | 250         | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | C00F                                                 | <a href="#">Samples</a> |
| SN74LVC1G00DCKR   | ACTIVE        | SC70         | DCK             | 5    | 3000        | RoHS & Green    | NIPDAU   SN                          | Level-1-260C-UNLIM   | -40 to 125   | (CA5, CAF, CAJ, CAK, CAR)<br>(CAH, CAP, CAS)         | <a href="#">Samples</a> |
| SN74LVC1G00DCKRE4 | ACTIVE        | SC70         | DCK             | 5    | 3000        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | CA5<br>CAS                                           | <a href="#">Samples</a> |
| SN74LVC1G00DCKRG4 | ACTIVE        | SC70         | DCK             | 5    | 3000        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | CA5<br>CAS                                           | <a href="#">Samples</a> |
| SN74LVC1G00DCKT   | ACTIVE        | SC70         | DCK             | 5    | 250         | RoHS & Green    | NIPDAU   SN                          | Level-1-260C-UNLIM   | -40 to 125   | (CA5, CAF, CAJ, CAK, CAR)<br>(CAH, CAP, CAS)         | <a href="#">Samples</a> |
| SN74LVC1G00DCKTG4 | ACTIVE        | SC70         | DCK             | 5    | 250         | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | CA5<br>CAS                                           | <a href="#">Samples</a> |
| SN74LVC1G00DPWR   | ACTIVE        | X2SON        | DPW             | 5    | 3000        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 125   | H4                                                   | <a href="#">Samples</a> |
| SN74LVC1G00DRLR   | ACTIVE        | SOT-5X3      | DRL             | 5    | 4000        | RoHS & Green    | NIPDAUAG                             | Level-1-260C-UNLIM   | -40 to 125   | (CA7, CAR)                                           | <a href="#">Samples</a> |
| SN74LVC1G00DRY2   | ACTIVE        | SON          | DRY             | 6    | 5000        | RoHS & Green    | NIPDAU   NIPDAUAG                    | Level-1-260C-UNLIM   | -40 to 125   | CA                                                   | <a href="#">Samples</a> |
| SN74LVC1G00DRYR   | ACTIVE        | SON          | DRY             | 6    | 5000        | RoHS & Green    | NIPDAU   NIPDAUAG                    | Level-1-260C-UNLIM   | -40 to 125   | CA                                                   | <a href="#">Samples</a> |

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2) | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|-----------------|--------------------------------------|----------------------|--------------|-------------------------|-------------------------|
| SN74LVC1G00DSF2  | ACTIVE        | SON          | DSF                | 6    | 5000           | RoHS & Green    | NIPDAU   NIPDAUAG                    | Level-1-260C-UNLIM   | -40 to 125   | CA                      | <a href="#">Samples</a> |
| SN74LVC1G00DSFR  | ACTIVE        | SON          | DSF                | 6    | 5000           | RoHS & Green    | NIPDAU   NIPDAUAG                    | Level-1-260C-UNLIM   | -40 to 125   | CA                      | <a href="#">Samples</a> |
| SN74LVC1G00YZPR  | ACTIVE        | DSBGA        | YZP                | 5    | 3000           | RoHS & Green    | SNAGCU                               | Level-1-260C-UNLIM   | -40 to 85    | (CA7, CAN)              | <a href="#">Samples</a> |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBsolete:** TI has discontinued the production of the device.

<sup>(2)</sup> **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

<sup>(3)</sup> MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

<sup>(4)</sup> There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

<sup>(5)</sup> Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

<sup>(6)</sup> Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF SN74LVC1G00 :**

- Enhanced Product : [SN74LVC1G00-EP](#)

## NOTE: Qualified Version Definitions:

- Enhanced Product - Supports Defense, Aerospace and Medical Applications

**TAPE AND REEL INFORMATION**


\*All dimensions are nominal

| Device            | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74LVC1G00DBVR   | SOT-23       | DBV             | 5    | 3000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DBVR   | SOT-23       | DBV             | 5    | 3000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DBVRG4 | SOT-23       | DBV             | 5    | 3000 | 178.0              | 9.0                | 3.23    | 3.17    | 1.37    | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DBVT   | SOT-23       | DBV             | 5    | 250  | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DBVT   | SOT-23       | DBV             | 5    | 250  | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DBVTG4 | SOT-23       | DBV             | 5    | 250  | 178.0              | 9.0                | 3.23    | 3.17    | 1.37    | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DCKR   | SC70         | DCK             | 5    | 3000 | 180.0              | 8.4                | 2.3     | 2.5     | 1.2     | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DCKRG4 | SC70         | DCK             | 5    | 3000 | 178.0              | 9.2                | 2.4     | 2.4     | 1.22    | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DCKT   | SC70         | DCK             | 5    | 250  | 178.0              | 9.2                | 2.4     | 2.4     | 1.22    | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DCKT   | SC70         | DCK             | 5    | 250  | 180.0              | 8.4                | 2.47    | 2.3     | 1.25    | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DCKT   | SC70         | DCK             | 5    | 250  | 178.0              | 9.0                | 2.4     | 2.5     | 1.2     | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DCKTG4 | SC70         | DCK             | 5    | 250  | 178.0              | 9.2                | 2.4     | 2.4     | 1.22    | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DPWR   | X2SON        | DPW             | 5    | 3000 | 178.0              | 8.4                | 0.91    | 0.91    | 0.5     | 2.0     | 8.0    | Q3            |
| SN74LVC1G00DRLR   | SOT-5X3      | DRL             | 5    | 4000 | 180.0              | 8.4                | 1.98    | 1.78    | 0.69    | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DRY2   | SON          | DRY             | 6    | 5000 | 180.0              | 8.4                | 1.65    | 1.2     | 0.7     | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DRY2   | SON          | DRY             | 6    | 5000 | 180.0              | 9.5                | 1.6     | 1.15    | 0.75    | 4.0     | 8.0    | Q3            |

| Device          | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74LVC1G00DRYR | SON          | DRY             | 6    | 5000 | 180.0              | 9.5                | 1.15    | 1.6     | 0.75    | 4.0     | 8.0    | Q1            |
| SN74LVC1G00DSF2 | SON          | DSF             | 6    | 5000 | 180.0              | 8.4                | 1.16    | 1.16    | 0.63    | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DSF2 | SON          | DSF             | 6    | 5000 | 180.0              | 9.5                | 1.16    | 1.16    | 0.5     | 4.0     | 8.0    | Q3            |
| SN74LVC1G00DSFR | SON          | DSF             | 6    | 5000 | 180.0              | 9.5                | 1.16    | 1.16    | 0.5     | 4.0     | 8.0    | Q2            |
| SN74LVC1G00YZPR | DSBGA        | YZP             | 5    | 3000 | 178.0              | 9.2                | 1.02    | 1.52    | 0.63    | 4.0     | 8.0    | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device            | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|-------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74LVC1G00DBVR   | SOT-23       | DBV             | 5    | 3000 | 210.0       | 185.0      | 35.0        |
| SN74LVC1G00DBVR   | SOT-23       | DBV             | 5    | 3000 | 210.0       | 185.0      | 35.0        |
| SN74LVC1G00DBVRG4 | SOT-23       | DBV             | 5    | 3000 | 180.0       | 180.0      | 18.0        |
| SN74LVC1G00DBVT   | SOT-23       | DBV             | 5    | 250  | 210.0       | 185.0      | 35.0        |
| SN74LVC1G00DBVT   | SOT-23       | DBV             | 5    | 250  | 210.0       | 185.0      | 35.0        |
| SN74LVC1G00DBVTG4 | SOT-23       | DBV             | 5    | 250  | 180.0       | 180.0      | 18.0        |
| SN74LVC1G00DCKR   | SC70         | DCK             | 5    | 3000 | 210.0       | 185.0      | 35.0        |
| SN74LVC1G00DCKRG4 | SC70         | DCK             | 5    | 3000 | 180.0       | 180.0      | 18.0        |
| SN74LVC1G00DCKT   | SC70         | DCK             | 5    | 250  | 180.0       | 180.0      | 18.0        |
| SN74LVC1G00DCKT   | SC70         | DCK             | 5    | 250  | 202.0       | 201.0      | 28.0        |
| SN74LVC1G00DCKT   | SC70         | DCK             | 5    | 250  | 180.0       | 180.0      | 18.0        |
| SN74LVC1G00DCKTG4 | SC70         | DCK             | 5    | 250  | 180.0       | 180.0      | 18.0        |
| SN74LVC1G00DPWR   | X2SON        | DPW             | 5    | 3000 | 205.0       | 200.0      | 33.0        |
| SN74LVC1G00DRLR   | SOT-5X3      | DRL             | 5    | 4000 | 202.0       | 201.0      | 28.0        |
| SN74LVC1G00DRY2   | SON          | DRY             | 6    | 5000 | 202.0       | 201.0      | 28.0        |
| SN74LVC1G00DRY2   | SON          | DRY             | 6    | 5000 | 184.0       | 184.0      | 19.0        |
| SN74LVC1G00DRYR   | SON          | DRY             | 6    | 5000 | 184.0       | 184.0      | 19.0        |
| SN74LVC1G00DSF2   | SON          | DSF             | 6    | 5000 | 202.0       | 201.0      | 28.0        |

---

| Device          | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|-----------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74LVC1G00DSF2 | SON          | DSF             | 6    | 5000 | 184.0       | 184.0      | 19.0        |
| SN74LVC1G00DSFR | SON          | DSF             | 6    | 5000 | 184.0       | 184.0      | 19.0        |
| SN74LVC1G00YZPR | DSBGA        | YZP             | 5    | 3000 | 220.0       | 220.0      | 35.0        |

## GENERIC PACKAGE VIEW

**DPW 5**




**X2SON - 0.4 mm max height**

PLASTIC SMALL OUTLINE - NO LEAD



Images above are just a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.

4211218-3/D



4223102/D 03/2022

## NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. The size and shape of this feature may vary.

# EXAMPLE BOARD LAYOUT

DPW0005A

X2SON - 0.4 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



LAND PATTERN EXAMPLE  
SOLDER MASK DEFINED  
SCALE:60X

4223102/D 03/2022

NOTES: (continued)


4. This package is designed to be soldered to a thermal pad on the board. For more information, refer to QFN/SON PCB application note in literature No. SLUA271 ([www.ti.com/lit/sluea271](http://www.ti.com/lit/sluea271)).

# EXAMPLE STENCIL DESIGN

DPW0005A

X2SON - 0.4 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



SOLDER PASTE EXAMPLE  
BASED ON 0.1 mm THICK STENCIL

EXPOSED PAD 3  
92% PRINTED SOLDER COVERAGE BY AREA UNDER PACKAGE  
SCALE:100X

4223102/D 03/2022

NOTES: (continued)

5. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.



YZP0005



# PACKAGE OUTLINE

DSBGA - 0.5 mm max height

DIE SIZE BALL GRID ARRAY



D: Max = 1.418 mm, Min = 1.358 mm  
E: Max = 0.918 mm, Min = 0.858 mm

4219492/A 05/2017

## NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.

# EXAMPLE BOARD LAYOUT


YZP0005

DSBGA - 0.5 mm max height

DIE SIZE BALL GRID ARRAY



LAND PATTERN EXAMPLE  
SCALE:40X




SOLDER MASK DETAILS  
NOT TO SCALE

4219492/A 05/2017

NOTES: (continued)

- Final dimensions may vary due to manufacturing tolerance considerations and also routing constraints. For more information, see Texas Instruments literature number SNVA009 ([www.ti.com/lit/snva009](http://www.ti.com/lit/snva009)).




SOLDER PASTE EXAMPLE  
 BASED ON 0.1 mm THICK STENCIL  
 SCALE:40X

4219492/A 05/2017

NOTES: (continued)

4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release.


DRL0005A



## PACKAGE OUTLINE

SOT - 0.6 mm max height

PLASTIC SMALL OUTLINE



4220753/D 07/2024

### NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. Reference JEDEC registration MO-293 Variation UAAD-1

# EXAMPLE BOARD LAYOUT


DRL0005A

SOT - 0.6 mm max height

PLASTIC SMALL OUTLINE



LAND PATTERN EXAMPLE  
SCALE:30X



SOLDERMASK DETAILS

4220753/D 07/2024

NOTES: (continued)


5. Publication IPC-7351 may have alternate designs.
6. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DRL0005A

SOT - 0.6 mm max height

PLASTIC SMALL OUTLINE



SOLDER PASTE EXAMPLE  
BASED ON 0.1 mm THICK STENCIL  
SCALE:30X

4220753/D 07/2024

NOTES: (continued)

7. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
8. Board assembly site may have different recommendations for stencil design.



### SOT - 1.1 max height

Technical drawing of a mechanical part showing three views: front, side, and top.

**Front View:**

- Overall dimensions: 2.4 (width) x 2.15 (height).
- Feature locations: 1.4, 1.1, 1.3, 1.3.
- Hole diameters: 0.15, 0.1.
- Feature 5: 5X 0.33 0.15.
- Feature 1: PIN 1 INDEX AREA (hatched area).
- Feature 4: (0.1).
- Feature 3: 5X 0.33 0.15.
- Feature 2: 2X 0.65.
- Feature 1: 1.3.
- Feature 5: 5X 0.33 0.15.
- Feature 4: 4X 0° -12°.
- Feature 3: 3X 0° -12°.
- Feature 2: 2X 0° -12°.
- Feature 1: 1X 0° -12°.

**Side View:**

- Overall width: 1.1 MAX.
- Thickness: 0.1.
- Feature 1: 1.1 MAX.
- Feature 2: 0.1.
- Feature 3: 0.1.
- Feature 4: 0.1.
- Feature 5: 0.1.

**Top View:**

- Overall width: 0.46 TYP.
- Overall height: 0.22 TYP.
- Feature 1: 0.15.
- Feature 2: 0.22 TYP.
- Feature 3: 0.08 TYP.
- Feature 4: 0.22 TYP.
- Feature 5: 0.08 TYP.
- Feature 6: 0.22 TYP.
- Feature 7: 0.08 TYP.
- Feature 8: 0.22 TYP.
- Feature 9: 0.08 TYP.
- Feature 10: 0.22 TYP.
- Feature 11: 0.08 TYP.
- Feature 12: 0.22 TYP.
- Feature 13: 0.08 TYP.
- Feature 14: 0.22 TYP.
- Feature 15: 0.08 TYP.
- Feature 16: 0.22 TYP.
- Feature 17: 0.08 TYP.
- Feature 18: 0.22 TYP.
- Feature 19: 0.08 TYP.
- Feature 20: 0.22 TYP.
- Feature 21: 0.08 TYP.
- Feature 22: 0.22 TYP.
- Feature 23: 0.08 TYP.
- Feature 24: 0.22 TYP.
- Feature 25: 0.08 TYP.
- Feature 26: 0.22 TYP.
- Feature 27: 0.08 TYP.
- Feature 28: 0.22 TYP.
- Feature 29: 0.08 TYP.
- Feature 30: 0.22 TYP.
- Feature 31: 0.08 TYP.
- Feature 32: 0.22 TYP.
- Feature 33: 0.08 TYP.
- Feature 34: 0.22 TYP.
- Feature 35: 0.08 TYP.
- Feature 36: 0.22 TYP.
- Feature 37: 0.08 TYP.
- Feature 38: 0.22 TYP.
- Feature 39: 0.08 TYP.
- Feature 40: 0.22 TYP.
- Feature 41: 0.08 TYP.
- Feature 42: 0.22 TYP.
- Feature 43: 0.08 TYP.
- Feature 44: 0.22 TYP.
- Feature 45: 0.08 TYP.
- Feature 46: 0.22 TYP.
- Feature 47: 0.08 TYP.
- Feature 48: 0.22 TYP.
- Feature 49: 0.08 TYP.
- Feature 50: 0.22 TYP.
- Feature 51: 0.08 TYP.
- Feature 52: 0.22 TYP.
- Feature 53: 0.08 TYP.
- Feature 54: 0.22 TYP.
- Feature 55: 0.08 TYP.
- Feature 56: 0.22 TYP.
- Feature 57: 0.08 TYP.
- Feature 58: 0.22 TYP.
- Feature 59: 0.08 TYP.
- Feature 60: 0.22 TYP.
- Feature 61: 0.08 TYP.
- Feature 62: 0.22 TYP.
- Feature 63: 0.08 TYP.
- Feature 64: 0.22 TYP.
- Feature 65: 0.08 TYP.
- Feature 66: 0.22 TYP.
- Feature 67: 0.08 TYP.
- Feature 68: 0.22 TYP.
- Feature 69: 0.08 TYP.
- Feature 70: 0.22 TYP.
- Feature 71: 0.08 TYP.
- Feature 72: 0.22 TYP.
- Feature 73: 0.08 TYP.
- Feature 74: 0.22 TYP.
- Feature 75: 0.08 TYP.
- Feature 76: 0.22 TYP.
- Feature 77: 0.08 TYP.
- Feature 78: 0.22 TYP.
- Feature 79: 0.08 TYP.
- Feature 80: 0.22 TYP.
- Feature 81: 0.08 TYP.
- Feature 82: 0.22 TYP.
- Feature 83: 0.08 TYP.
- Feature 84: 0.22 TYP.
- Feature 85: 0.08 TYP.
- Feature 86: 0.22 TYP.
- Feature 87: 0.08 TYP.
- Feature 88: 0.22 TYP.
- Feature 89: 0.08 TYP.
- Feature 90: 0.22 TYP.
- Feature 91: 0.08 TYP.
- Feature 92: 0.22 TYP.
- Feature 93: 0.08 TYP.
- Feature 94: 0.22 TYP.
- Feature 95: 0.08 TYP.
- Feature 96: 0.22 TYP.
- Feature 97: 0.08 TYP.
- Feature 98: 0.22 TYP.
- Feature 99: 0.08 TYP.
- Feature 100: 0.22 TYP.

**Notes:**

- NOTE 5: Feature control frame for circular feature.
- NOTE 4: Feature control frame for rectangular feature.


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Reference JEDEC MO-203.
4. Support pin may differ or may not be present.
5. Lead width does not comply with JEDEC.
6. Body dimensions do not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.25mm per side

# EXAMPLE BOARD LAYOUT


DCK0005A

SOT - 1.1 max height

SMALL OUTLINE TRANSISTOR



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:18X




SOLDER MASK DETAILS

4214834/F 08/2024

NOTES: (continued)

7. Publication IPC-7351 may have alternate designs.
8. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



4214834/F 08/2024

NOTES: (continued)

9. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
10. Board assembly site may have different recommendations for stencil design.



# EXAMPLE BOARD LAYOUT

DBV0005A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:15X



SOLDER MASK DETAILS

4214839/K 08/2024

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DBV0005A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:15X

4214839/K 08/2024

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## GENERIC PACKAGE VIEW

**DRY 6**

**USON - 0.6 mm max height**

PLASTIC SMALL OUTLINE - NO LEAD



Images above are just a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.

4207181/G




# EXAMPLE BOARD LAYOUT


DRY0006A

USON - 0.6 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



**LAND PATTERN EXAMPLE**  
1:1 RATIO WITH PKG SOLDER PADS  
EXPOSED METAL SHOWN  
SCALE:40X



**SOLDER MASK DETAILS**

4222894/A 01/2018

NOTES: (continued)


3. For more information, see QFN/SON PCB application report in literature No. SLUA271 ([www.ti.com/lit/sluea271](http://www.ti.com/lit/sluea271)).

## EXAMPLE STENCIL DESIGN

DRY0006A

USON - 0.6 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



SOLDER PASTE EXAMPLE  
BASED ON 0.075 - 0.1 mm THICK STENCIL  
SCALE:40X

4222894/A 01/2018

NOTES: (continued)

4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.




# EXAMPLE BOARD LAYOUT


DSF0006A

X2SON - 0.4 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:40X



SOLDER MASK DETAILS

4220597/B 06/2022

NOTES: (continued)


4. For more information, see Texas Instruments literature number SLUA271 ([www.ti.com/lit/sluea271](http://www.ti.com/lit/sluea271)).

## EXAMPLE STENCIL DESIGN

DSF0006A

X2SON - 0.4 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



SOLDER PASTE EXAMPLE  
BASED ON 0.09 mm THICK STENCIL

PRINTED SOLDER COVERAGE BY AREA UNDER PACKAGE  
SCALE:40X

4220597/B 06/2022

4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2024, Texas Instruments Incorporated